

Sani Table Plus



Free standing Sanification Device

Sanification boosted device wall mounted / free standing projected to eliminate airborne pathogens in all closed places till 40 m².

A perception of clean odor-free air is felt when entering in the place where the appliance is installed; the benefit is assured and durable over the time.

Simple switch on with central touch button and light setting mode.

Very silent, can be stand on in any flat surface and do not require any installation but just the simple energy connection.

Very low energy consumption; suggested 24 hours ongoing use for a total sanification effect of the room air and the surfaces.



Applications

For all closed places till 40 m²

Features

- Touch control
- Dimmable external central light
- Silent
- Low energy consumption
- Free maintenance
- No installation required

Available colours

■ black □ white

Optional

Bracket and internal driver for wall installation

Sani Table Plus

GENERAL FEATURES

Category	Air Sanitizer
Room (cover m ²)	up to 40
Materials	Painted steel structure Cover Plexiglass
Airflow capacity (m ³ /h)	30
Power absorbed (W)	10
Noise (dB)	20
Operating temperature (°C)	0 - 50
Voltage (V)	220 - 240 • with adapter external 12 V
Frequency (Hz)	50 - 60
N° NTP (non thermal plasma)	1
Led UVC	Yes
Photocatalyst	Yes
Type of inlet filter Type of outlet filter	Polyester long fiber lasting
Montage	Desk (Wall installation optional)
Control	External control button
Dimension (cm)	21(P) x 21(L) x 10,5(H)
Weight (Kg)	1,1



NANO
PROJECT

SPECIFIC FEATURES

VENTILATION CHARACTERISTICS

Capacity (m ³ /h)	15
N° fan	2
Speed (rpm)	3200
Pressure (Pa)	17,5
Outlet air	Grid n° 32 - 18 x 3 mm

CHARACTERISTICS OF THE LIGHTING SYSTEM

N° Led UVC	2
Wavelength (nm)	265 - 275 nm
Irradiation 3 cm (μW/cm ²)	700
Irradiation 10 cm (μW/cm ²)	83

PACKAGING

External measure (cm)	26(P) x 26(L) x 15(H)
Total Weight (Kg)	1,6

