

Sani Tower



Sanification Tower Device

Sanification tower device projected to eliminate airborne pathogens in the air in all closed places till 80 m².

A perception of clean odor-free air is felt when entering in the place where the appliance is installed; the benefit is assured and durable over the time.

Simple switch on with central touch button and light setting mode.

Very silent, can be stand on floor and do not require any installation but just the simple energy connection.

Very low energy consumption; suggested 24 hours ongoing use for a total sanification effect of the room air and the surfaces.



Applications

Offices, Hospitals, Gyms, Waiting Rooms, Classrooms, Clinics
Closed rooms up to 80 m²

Features

Touch key
Central light adjustment on the panel
Silent
Low energy consumption
No maintenance
No installation required

Colours available

■ black □ white

Sani Tower

GENERAL FEATURES

Category	Air Sanitizer
Room (cover m ²)	up to 80
Materials	Painted steel structure Cover Plexiglass
Airflow capacity (m ³ /h)	90
Power absorbed (W)	20
Noise (dB)	29
Operating temperature (°C)	0 - 50
Voltage (V)	220 - 240 • with adapter external 12 V
Frequency (Hz)	50 - 60
N° NTP (non thermal plasma)	2
Led UVC	Yes
Photocatalyst	Yes
Type of inlet filter Type of outlet filter	Polyester long fiber lasting
Montage	Floor
Control	External control button
Dimension (cm)	21(P) x 21(L) x 69(H)
Weight (Kg)	4,7



SPECIFIC FEATURES

VENTILATION CHARACTERISTICS

Capacity (m ³ /h)	90
N° fan	1
Speed (rpm)	1600
Pressure (Pa)	15
Outlet air	Grid n° 48 - 35 x 5 mm

CHARACTERISTICS OF THE LIGHTING SYSTEM

N° Led UVC	8
Wavelength (nm)	265 - 275 nm
Irradiation 3 cm (μW/cm ²)	838
Irradiation 10 cm (μW/cm ²)	206

PACKAGING

External measure (cm)	23(P) x 23(L) x 72(H)
Total Weight (Kg)	5,4

