

# Sani Lift Dual



## Purification Lift Device Bivalent

**P**urification Ceiling/Wall stainless steel bivalent device projected to eliminate airborne pathogens in the air into the Lifts.

The benefit is assured and durable over the time.  
Very silent, can be easily ceiling/wall installed.  
Very low energy consumption; suggested 24 hours ongoing use for a total purification effect of the room air and the surfaces.



### Applications

Lift

### Features

Silent  
Low energy consumption  
Double fan  
Free maintenance

### Colours available

Stainless Steel scotch brite finishing

## GENERAL FEATURES

Category	Air Purifier
Room (cover m <sup>2</sup> )	up to 12
Materials	Inox stainless steel structure scotch brite
Airflow capacity (m <sup>3</sup> /h)	18
Power absorbed (W)	3
Noise (dB)	25
Operating temperature (°C)	0 - 50
Voltage (V)	110 - 240
Frequency (Hz)	50 - 60
N° NTP (non thermal plasma)	No
Led UVC	Yes
Photocatalyst	Yes
Type of inlet filter Type of outlet filter	Polyester long fiber lasting Polyurethane fiber with activated carbon
Montage	Wall • Ceiling
Control	External control
Dimension (cm)	24(P) x 14(L) x 4,3(H)
Weight (Kg)	0,6

## Sani Lift Dual



## SPECIFIC FEATURES

## VENTILATION CHARACTERISTICS

Capacity (m <sup>3</sup> /h)	9
N° fan	2
Speed (rpm)	9500
Pressure (Pa)	37,3
Outlet air	Grid n° 20 - 18 x 3 mm

## CHARACTERISTICS OF THE LIGHTING SYSTEM

N° Led UVC	2
Wavelength (nm)	265 - 275 nm
Irradiation 3 cm (μW/cm <sup>2</sup> )	700
Irradiation 10 cm (μW/cm <sup>2</sup> )	83

## PACKAGING

External measure (cm)	25(P) x 26(L) x 12(H)
Total Weight (Kg)	1

