

# Sani Close Dual



## Purification Device for small close rooms Bivalent

**P**urification Free Standing/Ceiling/Wall Bivalent device projected to eliminate airborne pathogens in the air into small confined rooms

The benefit of the air treatment is assured and durable over the time. Very silent, can be easily backing or ceiling/wall installed.

Very low energy consumption; suggested 24 hours ongoing use for a total purification effect of the room air and the surfaces.



**NANO**  
PROJECT

### Applications

Wardrobe cabins,  
Camper vans, Boats, Taxis  
Small environments

### Features

Silent  
Low energy consumption  
Double fan  
Free maintenance

### Colours available

■ black □ white ■ dark brown ■ grey

### Optional

Alimentazione 12 V (Sani Close 12)

# Sani Close Dual

## GENERAL FEATURES

Category	Air Purifier
Room (cover m <sup>2</sup> )	up to 12
Materials	Painted steel structure
Airflow capacity (m <sup>3</sup> /h)	18
Power absorbed (W)	3
Noise (dB)	25
Operating temperature (°C)	0 - 50
Voltage (V)	110 - 240 (optional 12 V power supply)
Frequency (Hz)	50 - 60
N° NTP (non thermal plasma)	No
Led UVC	Yes
Photocatalyst	Yes
Type of inlet filter Type of outlet filter	Polyester long fiber lasting Polyurethane fiber with activated carbon
Montage	Desk • Wall • Ceiling
Control	External control
Dimension (cm)	24(P) x 14(L) x 4,3(H)
Weight (Kg)	0,6



## SPECIFIC FEATURES

### VENTILATION CHARACTERISTICS

Capacity (m <sup>3</sup> /h)	9
N° fan	2
Speed (rpm)	9500
Pressure (Pa)	37,3
Outlet air	Grid n° 20 - 18 x 3 mm

### CHARACTERISTICS OF THE LIGHTING SYSTEM

N° Led UVC	2
Wavelength (nm)	265 - 275 nm
Irradiation 3 cm (μW/cm <sup>2</sup> )	700
Irradiation 10 cm (μW/cm <sup>2</sup> )	83

### PACKAGING

External measure (cm)	25(P) x 26(L) x 12(H)
Total Weight (Kg)	1

